

10



11



12



(10) CSL

The LED Eco-Counter 2 is the next generation of the company's 120-volt LED Eco-Counter task light featuring the latest SSL technology. Recently upgraded to 90 CRI, the Eco-Counter 2 offers 50,000 hour lamp life at 70% lumen maintenance and has an integrated 120-volt system, eliminating the need for remote transformers or drivers. It has a low profile - only 7/8" high - and a glass lens with LED diffuser film. Captive screws and Speedlink™ technology (hardwire, portable, linkable) make for quick installation. The Speedlink system links a maximum of 24 units. The Eco-Counter 2 is cUL/UL-listed for damp locations and available in four lengths (8, 16, 24, and 32 inches with corresponding wattages) and can be ordered in either a White, Bronze, or Satin Aluminum finish. www.csllighting.com

(11) WILA

The WILA 640 LED linear is a low profile, linear, line-voltage LED cove fixture with an aluminum extrusion housing. It has highly efficient, color-consistent LEDs with an SDCM of 3. An opal lens allows for smooth and even illumination, eliminating pixilation and striations on the wall. The 640 is fully dimmable to 1 percent, has a 120° spread, and rivals fluorescent T8 strips' output with 500 delivered lumens per foot using only 8 watts and a choice of 3000K and 4000K CCT. www.wilalighting.com

(12) ACCESS LIGHTING

The IntelLED modular track system can provide undercabinet lighting as well as accent illumination for toe kicks, coves, display lighting, and wall grazing. It is available in 3000K or 4000K and in a variety of lengths and connection options. www.accesslighting.com