

ECO-COVE LED

Linkable Cove Lighting

ECV-10
ECV-20

FEATURES

- Integrated 120V linkable system – no external remote transformers or drivers
- Linkable up to 100'
- UL/C-UL listed for wet location (IP67)



LEDs

- Two light colors:
 - 2,700°K ±50
 - 4,000°K ±50
- Long life, low maintenance
- 50,000-hour lamp life @ 70% lumen maintenance (L70)
- Two sizes:
 - 10.5" length- 6W, 400 lm
 - 21" length- 12W 800 lm
- Compatible with Electronic Low-Voltage (ELV) dimmers (consult factory for compliance)

ECV-10 SERIES

10.5" L x 1.5" W x 1.75" H

6W, 400lm, Compatible with INC (incandescent/triac) & ELV dimmers

- ECV-10-27-2 2,700°K, ±50, 400lm, CRI 90
- ECV-10-40-2 4,000°K, ±50, 400lm, CRI 80

HOUSING / HEAT SINK

- Adjustable – 120° total rotation
- Brushed aluminum extruded heat sink
- Polycarbonate lens
- PVC driver housing
- Stainless steel mounting brackets



Adjustable 120° Total Rotation

CONNECTORS AND POWER FEED

NUMBER	LENGTH	DESCRIPTION
• ECV-CON-1	1'	1' Connector
• ECV-CON-5	5'	5' Connector
• ECV-CON-10	10'	10' Connector
• ECV-PWR-20	20'	20' Power Feed



Project Notes

ECV-20 SERIES

21" L x 1.5" W x 1.75" H

12W, 800lm, Compatible with INC (incandescent/triac) & ELV dimmers

- ECV-20-27-2 2,700°K, ±50, 800lm, CRI 90
- ECV-20-40-2 4,000°K, ±50, 800lm, CRI 80



A Division of Troy-CSL

14508 Nelson Avenue City of Industry, CA 91744 Tel 626-336-4511 Fax 626-336-4266 www.csllighting.com

Rev 0516